a his

SET DINELENGUE 78

(THERMODOUFIE(4A) NUARIZ)(6A)(ALUMINUM(W)OXIDE

(THERMOCOUPLE(8A) QUARTZ)(P)(ALUMINUM(W)OXIDE)

(THERMUCOUPLE (SA) QUARTZ) (P) (ALUMINA)

QUARIZ(SA) TUBE AND (ALUMINUM(W) OXIDE OR ALUM)

21/ S (QUARTZ(SA) (UBE)(F)(ALUMINUM(W)OXIDE OR ALUMI

34 S (QUARIZ(SA) (USE) AND (ALUMINUM(W)OXIDE OR ALU

3 S L6 AND THERMOCOUPLE

02 FEB 88 10:5/:10

U.S. Patent & Irademark Uffice

H0903/

=> d 13 1-5

- 1.7 4,692,556, Sep. 8, 1987, Repeating temperature sensing immersion probe; Theo P. C. Boilen, et al., 136\*234, 232 LIMAGE AVAILABLE
- 2. 4,358,630, Nov. 9, 1982, Replacement cap for repeating use thermocouple; Richard A. Falk, 136\*234, 242; 3/4\*139 LIMAGE AVAILABLES
- 3. 4,284,7/1, Aug. 18, 1981, Process for preparing melamine; Hsuan L. Hen, et al., 544\*200
  - 4. 4,123,498, Uct. 31, 1978, Process for separating fission product molybdenum from an irradiated target material; Herman S. Rosenbaum, et al., 423\*2, 59 LIMAGE AVAILABLET
  - 3,958,1/6, May 18, 19/6, Method for measuring suitability of aluminum for U.S. Patent & Trademark Uffice 02 FEB 88 10:57:44

use in certain propellants; Karl J. Kraeutle, 324\*65R; /3\*35; 3/4\*5/

⇒> d 1/ 1−3

- 1. 4.692,556, Sep. B. 1987, Repeating temperature sensing immersion probe; Theo P. U. Boilen, et al., 136\*234, 232 LIMAGE AVAILABLEJ
- 2. 4,244,935, Jan. 13, 1981, Method of forming metal chlorides; M. Benjamin Dell, 423\*491, 137, 492, 493, 494, 496; 42/\*221
- 3. 4,059,418, Nov. 22, 19//, Flue gas desulturization sorbent and process; Neville L. Cuil, 55\*/3, /4; 423\*244 . 4

6)

11-10° 41.

## (FILE LISPAT)

		S	1	FAGE	LENGTH 19		
		SI		INE	LENGTH 78		
L1	102	S	OX.	YGEN	(W) SENSOR	AND	THERMOCOUPLE
L2	. 16	S	L 1	AND	MOLTEN		· · · · · · · · · · · · · · · · · · ·
L3	Ø	S	L.1	AND	U-TUBE		
L4	Ø	S	L1	AND	U(W) TUBE		
L5				4) TUI			
L6	64	S	L.5	AND	THERMOCOL	JPLE	
L.7					OXYGEN (W)		SOF
LB					73/CLAS C		
L9	16	S	L1	AND)	(73/CLAS	OR 3	74/CLAS)

=> d 12 1-16

- 1. 4,717,463, Jan. 5, 1988, Oxygen sensor; Harry G. Clauss, 204\*422, 423
- 2. 4,708,783, Nov. 24, 1987, Apparatus for the determination of silicon in molten metal: Hajime Nakamura, et al.,  $204 \pm 423$
- 3. 4,659,435, Apr. 21, 1987, Integrally heated electrochemical cell method
- and apparatus; Jack A. Brothers, et al., 204\*1T, 274, 406, 425, 426, 427
- 4. 4,657,641, Apr. 14, 1987, Determination of silicon in molten metal; Hajime Nakamura, et al., 204\*1T, 422
- 5. 4,644,138, Feb. 17, 1987, Temperature control system with simplified controller and power supply; Paul L. Walsh, 219\*501; 204\*1T; 219\*497; 323\*245; 330\*75, 103
- 6. [4,627,892], Dec. 9, 1986, Electrochemical sensors and methods for their manufacture and use; Wayne L. Worrell, et al.,  $2\emptyset4*1T$ , 422;  $264*57\emptyset$ ;  $5\emptyset1*1\emptyset3$ , 152
- 7. 4,451,350, May 29. 1984, Sensor for measuring density of oxygen in molten metal; Yutaka Tsuchida, et al., 204\*422, 423
- 8. 4,429,4 $\emptyset$ 2, Jan. 31, 1984, Devices for use in a glass-melting furnace;

Harold J. Carley, 373\*37

- 9. [4,342,633, Aug. 3, 1982, Oxygen sensor; Omer Cure, 204\*423
- 10. 4,313,799, Feb. 2, 1982, Oxygen sensor and method for determining the oxygen activity in molten glass; Richard A. Perkins, 204\*1T, 422
- 11. 4,264,423, Apr. 28, 1981, Fluidic thermistor/fugacity device; Taki Negas, et al., 204\*408, 1T, 427
- .12. 4,229,211, Oct. 21, 1980, Ladle heating system; Donald D. Battles, 266\*44; 75\*46; 266\*141, 281, 901; 432\*9, 10, 224, 225
- 13. 4,182,666, Jan. 8, 1980, Oxygen sensors; Thomas Dickinson, et al., 204\*412, 415
- 14. 4,133,036, Jan. 2. 1979. Method and system for monitoring a physical
- condition of a medium; Robert G. Watson, 364\*477; 136\*234; 164\*4.1; 340\*347AD; 364\*551, 557; 374\*107, 139 [IMAGE AVAILABLE]
- 15. 3,920,447, Nov. 18, 1975, Steel production method; David L. Schroeder, et al., 75\*43, 59.14, 59.16; 266\*80, 82, 87
- (16. 3,891,512, Jun. 24, 1975, Determination of oxygen in molten steel: Paul L. Jackson, 204\*1T, 422